

SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

[SYSTEM AND METHOD FOR DESIGN, DEVELOPMENT, AND DEPLOYMENT OF DISTRIBUTED APPLICATIONS THAT SHARE DATA FROM HETEROGENEOUS AND AUTONOMOUS SOURCES OVER THE WEB]

Background of Invention

[0001] With the advent of Internet and Web, Information Technology solutions for enterprise are moving toward a new era. Web Services makes distributed applications over the Web possible. In the data sharing and integration front, new standards are needed in order to provide consistent and scalable access to heterogeneous data sources with an entirely new programming model for data access. They should support disconnected data architecture, separation of data access and data manipulation, tight integration with XML, and the ability to combine data from multiple and varied sources. All these features lay the basis for a creative approach to data-sharing applications in the distributed environment of the Web and Internet. However, many issues need to be resolved in order to achieve the ultimate system and environment. The invention addresses the following issues:

[0002]

1. Integrated access to heterogeneous data sources. The ability to access data that resides in multiple autonomous and heterogeneous data sources, in a uniform and integrated manner, is now becoming very important for software development. Apart from system-level incompatibilities between different database systems,

[0004] 3. Tight integration with XML. Currently, there is an increasing interest in building information integration applications with an XML-based middleware. XML is a W3C standard designed to facilitate data exchange between Web-based applications. It allows a natural representation of data coming from any kinds of source, ranging from

well-structured database to semi-structured document management systems. In addition, XML facilitates interoperability between the various components of an integrated system. However, use of XML as a middleware integration technology still raises a number of pending issues, among which a serious problem is lacking of effective and efficient ways for conversion between XML streams and data in various existing sources. For example, DOM (Document Object Model) requires that an entire XML document be represented as a tree in the memory. This can be a heavy weight operation even for medium-sized files in terms of memory utilization. To make it worse, paging and swapping would cause serious performance degradation when the tree becomes larger than the size of available physical memory. On the other hand, SAX (Simple API for XML) substitutes an event-driven and procedural model for the object-oriented framework of DOM. SAX is able to process XML documents as streams, acting upon each element and content as it is encountered. But it cannot catch the data structures represented by XML documents; SAX itself is blind to the most of what is interesting about XML. Therefore, it is very much desirable that, in our solution for data access, the XML streams also be treated in a uniformed fashion. Conversion between data in XML format and our internal structure for data manipulation should be fully automated, requiring minimum programming effort. Furthermore, this conversion must be based on a formal specification for the syntax of the XML data, namely XML Schema.

- [0005] 4. Data exchange via the Web and Internet . The Internet, together with World Wide Web, has provided an opportunity to unite geographically dispersed users and computing resources into an integrated computing environment. The key to providing such an environment is to develop such a mechanism that allows users to transparently share data from the various sources over the Web. In addition to support integration of heterogeneous data, we need further to supply a built-in mechanism for data exchange via the Web and Internet. With such a mechanism, channels ought to be easily established, through which data is transferred in a standard format between its suppliers and consumers. Ideally, a proxy should be automatically created that provides a local access to the remote data object so that the programmers may concentrate on the business logic without having to worry about the communication details.

[0006]

[0007]

Summary of Invention

[0008]

[0009]

systems. In reality, however, many standards of this kind have been established for various vertical industries. Then, the infrastructure for the data sharing can be automatically built up according to the XML-based standard. In this process, an object of in-memory, relational data structure is created in each participating sub-systems that is consistent with the XML-based standard. This construct allows the participating sub-systems to share data in the way that they have agreed upon. Finally, Web-based remote method invocation facilitates a request/response mechanism whereby the data is transferred between the participating sub-systems. In this communication, XML messages carry the data that confined with the original standard. In this sense, our XML-based standard also serves as the transfer syntax. In addition, the objects for data sharing are working with disconnected set of data. Database connection is opened only when an object needs to be synchronized with its data source. As soon as the database operation is completed, the database connection can be closed again. Therefore, distributed applications that share data from heterogeneous and autonomous sources over the Web can be realized with modest computational resources.

[0010] 2. Programming Model. With our programming model, Web-based data-sharing applications are designed and implemented in an object-oriented fashion. An extendable class library is also supplied that simplifies the development tasks. Because distributed processing on the Web is a very active area in research and development, our programming model supports a flexible framework for adopting new innovations in this field.

[0011] 3. Tool Kit. A GUI-based tool kit that supports installation, customization, and administration of the Web-based data-sharing application systems. It will also be used to set-up problem-oriented distributed queries and distributed transactions.

[0012] 4. Server Product . A light-weighted data-consolidation server is a part of our solution. It accommodates the infrastructure for Web-based data sharing and only connects to the database in a participating sub-system when synchronization is needed.

Brief Description of Drawings

- [0013] FIG. 1 is a block diagram showing middle tier for integrated access to heterogeneous data.
- [0014] FIG. 2 is a block diagram illustrating the in-memory data structures that are created based on the XML Schema Definition (XSD) of the data-exchange standard.
- [0015] FIG. 3 is a block diagram illustrating XML Web services for data sharing over the Web.
- [0016] FIG. 4 is a block diagram detailing how to display data from different sources on a Web page.

Detailed Description

- [0017] The present invention is embodied in an XML-based middle tier whereby data-sharing applications in the distributed environment of the Internet and Web may be easily developed.
- [0018] As a part of this invention, interfaces are implemented that synchronizes the content of in-memory data structure and various data sources.
- [0019] An XML standard is designed as the global schema for data sharing in distributed environment, based on which the corresponding in-memory data structures are created for local data processing in the participating sub-systems. Furthermore, the XML standard also serves as the transfer syntax when the content of the in-memory data are exchanged between the participating sub-systems. The equivalency between the XML-based standard for data sharing and the in-memory data structure for data manipulation is the foundation of the invention.
- [0020] The XML-based middle tier in our invention for data sharing in distributed environment provides global applications with a consistent view of data in various sources.
- [0021] Logically, the middle tier is composed of an in-memory data structure and an interface to the data source. While the in-memory data architecture has no knowledge of the data source behind it, it is the interface to the database that populates the in-memory data structure and resolves updates with the data source.

[0022] Physically, the middle tier may be implemented in the following ways.

[0023] • The middle tier is implemented within the sub-system.

[0024] • The middle tier is implemented as a front-end on a separate hardware platform.

[0025] If Microsoft ADO.NET technology is used, the middle tier may be implemented with sub-systems that support Microsoft .NET Framework. For sub-system that does not support Microsoft .NET Framework, a separated front-end is implemented through which the sub-system can join the distributed data sharing environment. Our solution and programming model may be implemented under different platforms. For example, it can also be implemented with J2EE standards.

[0026] This construct is depicted in FIG. 1. In this figure, the middle tier for sub-system 1 is implemented within the sub-system, while those for sub-system 2 and 3 are implemented in separate hardware platform.

[0027] Traditional client/server application maintains a connection to a database during its lifetime. This approach would cause serious performance and scalability in Web-based applications. The XML-based middle tier in our invention works with disconnected set of data in the in-memory data structure. Distributed data sharing over the Web can be realized with modest computational resources.

[0028] Due to the equivalency, data in format of the XML-based standard for data sharing and that the in-memory data structure for data manipulation can be converted back and forth automatically in our invention. Therefore, the middle tier may be design and implemented in the following ways for a specific distributed application as shown in FIG. 2.

[0029] • The XML-based standard for data sharing in the form of XSD, XML Schema is first defined, and the in-memory data structure can then be create by inferring the data relations embedded in the XSD. This method is very much useful as many XML-based standards for data sharing have been set up for various industries.

[0030] • The relational construction of the in-memory data structure is first defined and the XML-based standard for data sharing may be derived from the definition of the in-memory data structure. In addition, data in the in-memory data structures can thus

scheme may support various kind transactions, including short-time transactions for business applications with constraints of atomicity, consistency, isolation, and durability, such as fund transfer, and long-time transaction with semantic-based integrity rule and data sharing for cooperative applications, such as CAD/CAM and joint software development.